

Fluke 45 Dual Display Multimeter

| General Specifications | |
|--|---|
| VDC | Range: 0V-1000V Resolution: 1 \diamond V-0.01V Best Accuracy: \diamond 0.025% + 2* |
| VAC (True-rms, AC Coupled) Freq. 20 Hz-100 khz | Range: 0V-750V Resolution: 1 \diamond V-0.01V Best Accuracy: \diamond 0.2% + 10* |
| dB Readout (600 ? Ref.) (Ref. Z 2?-8000?) | Range: -34 \diamond 60 Resolution: 0.01 dB-0.1 dB Best Accuracy: \diamond 0.08 dBm * |
| ADC | Range: 0 mA-10A Resolution: 0.1 \diamond A-10 mA Best Accuracy: \diamond 0.05% + 2 * |
| AAC (True-rms, AC Coupled) Freq. 20 Hz-20 khz | Range: 15 \diamond A-10A Resolution: 0.1 \diamond A-10 mA Best Accuracy: \diamond 0.5% + 10 * |
| Resistance | Range: 0-100 MOhms Resolution: 0.001-1mOhms Best Accuracy: \diamond 0.05% + 2 * |
| Frequency | Range: 5 Hz - 1 MHz Resolution: .01 Hz-1 kHz Best Accuracy: \diamond 0.05% + 1 * |
| Size | 216 mm W x 93 mm H x 286 mm D (8.5" W x 3.67" H x 11.27" D) |
| Weight | Net 2.4 kg (5.2 lb); with battery 3.2 kg (7 lb) |
| One Year Warranty | One year calibration interval |

*Medium reading rate