

Fluke 45 Dual Display Multimeter

General Specifications	
VDC	Range: 0V-1000V Resolution: 1 \diamond V-0.01V Best Accuracy: \diamond 0.025% + 2*
VAC (True-rms, AC Coupled) Freq. 20 Hz-100 khz	Range: 0V-750V Resolution: 1 \diamond V-0.01V Best Accuracy: \diamond 0.2% + 10*
dB Readout (600 ? Ref.) (Ref. Z 2?-8000?)	Range: -34 \diamond 60 Resolution: 0.01 dB-0.1 dB Best Accuracy: \diamond 0.08 dBm *
ADC	Range: 0 mA-10A Resolution: 0.1 \diamond A-10 mA Best Accuracy: \diamond 0.05% + 2 *
AAC (True-rms, AC Coupled) Freq. 20 Hz-20 khz	Range: 15 \diamond A-10A Resolution: 0.1 \diamond A-10 mA Best Accuracy: \diamond 0.5% + 10 *
Resistance	Range: 0-100 MOhms Resolution: 0.001-1mOhms Best Accuracy: \diamond 0.05% + 2 *
Frequency	Range: 5 Hz - 1 MHz Resolution: .01 Hz-1 kHz Best Accuracy: \diamond 0.05% + 1 *
Size	216 mm W x 93 mm H x 286 mm D (8.5" W x 3.67" H x 11.27" D)
Weight	Net 2.4 kg (5.2 lb); with battery 3.2 kg (7 lb)
One Year Warranty	One year calibration interval

*Medium reading rate